

## Technical Specification NRS 90268

Module measured in Amplifier CL1600.

Note: 0dBu = 0,775V

### Channel A

#### Lo-Cut

Function	Lo-Cut-Filter
Frequency	31Hz
Filter type	12dB, Butterworth

#### LPN

Function	LPN-Filter
Frequency	100Hz
Filter type	12dB, LPN

### Channel B

#### Lo-Cut

Function	Lo-Cut-Filter
Frequency	31Hz
Filter type	12dB, Butterworth

#### LPN

Function	LPN-Filter
Frequency	100Hz
Filter type	12dB, LPN

**Gain Range**  $-\infty \dots +6\text{dB}$

**Frequency Response**  
**-3dB ref. 1kHz** 100Hz – 42kHz

S/N Ratio, note: module  
in CL1600 amplifier,  
A-weighted >108dB

**Dynamic Range,**  
**measured at module output,**  
**A-weighted, +20dBu** >114dB

**THD+N** < 0,05%

**Supply Voltage**  $\pm 15\text{Vdc}$

**Supply Current**  $\pm 24\text{mA}$

**Dimensions, (WxHxD), mm** 120 x 50 x 75

**Weight** 180g

## LPN & Lo-Cut

TELEX/EVI-AUDIO

Frequency Response

