



P.AUDIO SYSTEM CO., LTD.

19/4,6,7 Moo2, Putthamonthon 5 Road, Bangkratuek, Sampran, Nakornpathom 73210
Tel : (662) 441-6600 (Auto 30 line) Fax : (662) 441-6698-9
E-mail : info@paudiothailand.com Website : www.paudiothailand.com

NEW PRODUCTS 2014

Paging Horns

TH-18/TH-18M (with transformer)

| | |
|------------------------------|----------------------------------|
| Type | Reflex Horn Speaker |
| Power | 30 Watts |
| Sensitivity | Over 110 dB |
| Frequency Response | 200 Hz – 6 kHz |
| Nominal Coverage Angle | 40° (Conical) |
| Dimension | 496.1mm x 461.8mm 19.5"x18.2" |
| Finish Color | Ivory |
| Component | 1 x TH-18 |
| Construction | Press Aluminum |
| Unit Weight | 4 kg (8.8 lbs) |
| Shipping Weight | 4.2 kg (9.3 lbs) |
| Packing Dimension HxWxD (cm) | 51 x 51 x 50 (4.6 cu.ft) |

TH-15/TH-15M (with transformer)

| | |
|------------------------------|----------------------------------|
| Type | Reflex Horn Speaker |
| Power | 15 Watts (100 V Line) |
| Sensitivity | Over 106 dB |
| Frequency Response | 250 Hz – 7 kHz |
| Nominal Coverage Angle | 40° (Conical) |
| Dimension | 397.1mm x 373.9mm 15.6"x14.7" |
| Finish Color | Ivory |
| Component | 1 x TH-15 |
| Construction | Press Aluminum |
| Unit Weight | 3.4 kg (7.5 lbs) |
| Shipping Weight | 3.6 kg (8 lbs) |
| Packing Dimension HxWxD (cm) | 41 x 41 x 40 (2.37 cu.ft) |





P.AUDIO SYSTEM CO., LTD.

19/4,6,7 Moo2, Putthamonthon 5 Road, Bangkratuek, Sampran, Nakornpathom 73210
Tel : (662) 441-6600 (Auto 30 line) Fax : (662) 441-6698-9
E-mail : info@paudiothailand.com Website : www.paudiothailand.com

NEW PRODUCTS 2014

Paging Horns

TH-300

| | |
|------------------------------|------------------------------------|
| Nominal Impedance | 8 or 16 Ohm |
| Power | 300 Watt |
| Sensitivity | Over 130 dB |
| Frequency Response | 200 Hz – 7 kHz |
| Nominal Coverage Angle | 40° (Conical) |
| Dimension | Ø 484mm x 518mm Ø 19.1" x 20.4" |
| Finish Color | Black or White |
| Component | 4 x PA-D110 |
| Construction | Press Aluminum |
| Unit Weight | 17.6 kg (38.7 lbs) |
| Shipping Weight | 22.8 kg (50.2 lbs) |
| Packing Dimension HxWxD (cm) | 52 x 52 x 58 (5.8 cu.ft) |

TH-200 II

| | |
|------------------------------|------------------------------------|
| Nominal Impedance | 8 or 16 Ohm |
| Power | 200 Watt |
| Sensitivity | Over 127 dB |
| Frequency Response | 200 Hz – 7 kHz |
| Nominal Coverage Angle | 40° (Conical) |
| Dimension | Ø 352mm x 376mm Ø 13.9" x 14.8" |
| Finish Color | Black or White |
| Component | 2 x PA-D110 |
| Construction | Press Aluminum |
| Unit Weight | 9.4 kg (20.7 lbs) |
| Shipping Weight | 10.4 kg (22.9 lbs) |
| Packing Dimension HxWxD (cm) | 40 x 40 x 45 (2.5 cu.ft) |





P.AUDIO SYSTEM CO., LTD.

19/4,6,7 Moo2, Putthamonthon 5 Road, Bangkratuek, Sampran, Nakornpathom 73210
Tel : (662) 441-6600 (Auto 30 line) Fax : (662) 441-6698-9
E-mail : info@paudiothailand.com Website : www.paudiothailand.com

NEW PRODUCTS 2014

Foreground/Background



VS-8CX

| | |
|-----------------------|--|
| Type | 8 Inch Coaxial Full Range Speaker |
| Power | 175 Watts |
| Nominal Impedance | 8 Ohms |
| Sensitivity (1W@1M) | 93 dB |
| Frequency Response | 60 Hz - 20 KHz |
| Nominal Dispersion | 90° H x 90° V |
| Dimension (H x W x D) | 282mm x 282mm x 267mm (11" x 11" x 10") |



VS-8F

| | |
|-----------------------|--|
| Type | Two Way Full Range Bass Reflex |
| Power | 175 Watts |
| Nominal Impedance | 8 Ohms |
| Sensitivity (1W@1M) | 93 dB |
| Frequency Response | 60 Hz - 20 KHz |
| Nominal Dispersion | 60° H x 100° V |
| Dimension (H x W x D) | 422.1mm x 237.1mm x 250.5mm (16.6" x 9.3" x 9.8") |



VS-6F

| | |
|-----------------------|--|
| Type | Two Way Full Range Bass Reflex |
| Power | 100 Watts |
| Nominal Impedance | 8 Ohms |
| Sensitivity (1W@1M) | 92 dB |
| Frequency Response | 75 Hz - 18 KHz |
| Nominal Dispersion | 90° H x 60° V |
| Dimension (H x W x D) | 372.1mm x 194.1mm x 230.5mm (14.6" x 7.6" x 7.7") |



VS-5F

| | |
|-----------------------|---|
| Type | Full Range Acoustic Suspension |
| Power | 75 Watts |
| Nominal Impedance | 4 Ohms |
| Sensitivity (1W@1M) | 88 dB |
| Frequency Response | 65 Hz - 12 kHz |
| Nominal Dispersion | 90° H x 90° V |
| Dimension (H x W x D) | 191.4mm x 191.4mm x 195.1mm (7.5" x 7.5" x 7.7") |